

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product Description: **Ethanol, denat. with 5% wood spirit**  
 Cat No. : **365780000; 365780010**  
 Synonyms Ethyl alcohol  
 CAS No 64-17-5  
 EC No 200-578-6  
 Molecular Formula C2 H6 O

Unique Formula Identifier (UFI) **J5KT-6T62-TW01-EHPX**

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.  
 Uses advised against No Information available

### 1.3. Details of the supplier of the safety data sheet

#### Company

**UK entity/business name**  
 Fisher Scientific UK  
 Bishop Meadow Road,  
 Loughborough, Leicestershire LE11 5RG, United Kingdom

**EU entity/business name**  
 Thermo Fisher Scientific  
 Janssen Pharmaceuticaaan 3a, 2440 Geel, Belgium

E-mail address [begele.sdsdesk@thermofisher.com](mailto:begele.sdsdesk@thermofisher.com)

### 1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11  
 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99  
**CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

#### Poison Centre - Emergency information services

**Ireland** : National Poisons Information Centre (NPIC) -  
**01 809 2166** (8am-10pm, 7 days a week)  
**Malta** : +356 2395 2000  
**Cyprus** : +357 2240 5611

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Physical hazards

# SAFETY DATA SHEET

Ethanol, denat. with 5% wood spirit

Revision Date 29-Sep-2023

Flammable liquids	Category 2 (H225)
<b>Health hazards</b>	
Acute oral toxicity	Category 4 (H302)
Serious Eye Damage/Eye Irritation	Category 2 (H319)
Specific target organ toxicity - (single exposure)	Category 2 (H371)
<b>Environmental hazards</b>	
Based on available data, the classification criteria are not met	

Full text of Hazard Statements: see section 16

## 2.2. Label elements



Signal Word

Danger

## Hazard Statements

- H225 - Highly flammable liquid and vapor
- H302 - Harmful if swallowed
- H319 - Causes serious eye irritation
- H371 - May cause damage to organs

## Precautionary Statements

- P312 - Call a POISON CENTER or doctor if you feel unwell
- P264 - Wash face, hands and any exposed skin thoroughly after handling
- P280 - Wear eye protection/ face protection
- P337 + P313 - If eye irritation persists: Get medical advice/attention
- P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

## 2.3. Other hazards

This product does not contain any known or suspected endocrine disruptors

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
Ethyl alcohol	64-17-5	200-578-6	95	Flam. Liq. 2 (H225)

# SAFETY DATA SHEET

Ethanol, denat. with 5% wood spirit

Revision Date 29-Sep-2023

Methyl alcohol	67-56-1	200-659-6	5	Eye Irrit. 2 (H319) Flam. Liq. 2 (H225) Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370)
----------------	---------	-----------	---	---

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Ethyl alcohol	Eye Irrit. 2 :: C>=50%	-	-
Methyl alcohol	STOT Single Exp. 1 :: >= 10 STOT Single Exp. 2 :: 3 - < 10	-	-

Full text of Hazard Statements: see section 16

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

<b>General Advice</b>	If symptoms persist, call a physician.
<b>Eye Contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
<b>Skin Contact</b>	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
<b>Ingestion</b>	Clean mouth with water and drink afterwards plenty of water.
<b>Inhalation</b>	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.
<b>Self-Protection of the First Aider</b>	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

### 4.2. Most important symptoms and effects, both acute and delayed

. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes to Physician** Treat symptomatically. Symptoms may be delayed.

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

#### Suitable Extinguishing Media

Water spray. Carbon dioxide (CO<sub>2</sub>). Dry chemical. Chemical foam. Water mist may be used to cool closed containers.

#### Extinguishing media which must not be used for safety reasons

No information available.

### 5.2. Special hazards arising from the substance or mixture

Flammable. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may

# SAFETY DATA SHEET

Ethanol, denat. with 5% wood spirit

Revision Date 29-Sep-2023

explode when heated. Vapors may form explosive mixtures with air.

## **Hazardous Combustion Products**

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>).

### **5.3. Advice for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

### **6.2. Environmental precautions**

Do not flush into surface water or sanitary sewer system.

### **6.3. Methods and material for containment and cleaning up**

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

### **6.4. Reference to other sections**

Refer to protective measures listed in Sections 8 and 13.

## **SECTION 7: HANDLING AND STORAGE**

### **7.1. Precautions for safe handling**

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

### **Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

### **7.2. Conditions for safe storage, including any incompatibilities**

Keep in a dry, cool and well-ventilated place. Keep container tightly closed. Keep away from heat, sparks and flame. Flammables area.

**Technical Rules for Hazardous Substances (TRGS) 510**      Class 3  
**Storage Class (LGK) (Germany)**

### **7.3. Specific end use(s)**

Use in laboratories

ACR36578

# SAFETY DATA SHEET

Ethanol, denat. with 5% wood spirit

Revision Date 29-Sep-2023

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Ethyl alcohol	TWA: 1000 ppm TWA; 1920 mg/m <sup>3</sup> TWA WEL - STEL: 3000 ppm STEL; 5760 mg/m <sup>3</sup> STEL		STEL: 1000 ppm 15 min
Methyl alcohol	WEL - TWA: 200 ppm TWA; 266 mg/m <sup>3</sup> TWA WEL - STEL: 250 ppm STEL; 333 mg/m <sup>3</sup> STEL	TWA: 200 ppm 8 hr TWA: 260 mg/m <sup>3</sup> 8 hr Skin	TWA: 200 ppm 8 hr. TWA: 260 mg/m <sup>3</sup> 8 hr. STEL: 600 ppm 15 min STEL: 780 mg/m <sup>3</sup> 15 min Skin

#### Biological limit values

List source(s):

#### Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Oral)	Acute effects systemic (Oral)	Chronic effects local (Oral)	Chronic effects systemic (Oral)
Ethyl alcohol 64-17-5 ( 95 )		DNEL = 87 mg/kg bw/d		

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Ethyl alcohol 64-17-5 ( 95 )				DNEL = 343mg/kg bw/day
Methyl alcohol 67-56-1 ( 5 )		DNEL = 20mg/kg bw/day		DNEL = 20mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Ethyl alcohol 64-17-5 ( 95 )	DNEL = 1900mg/m <sup>3</sup>			DNEL = 950mg/m <sup>3</sup>
Methyl alcohol 67-56-1 ( 5 )	DNEL = 130mg/m <sup>3</sup>	DNEL = 130mg/m <sup>3</sup>	DNEL = 130mg/m <sup>3</sup>	DNEL = 130mg/m <sup>3</sup>

#### Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Methyl alcohol 67-56-1 ( 5 )	PNEC = 20.8mg/L	PNEC = 77mg/kg sediment dw	PNEC = 1540mg/L	PNEC = 100mg/L	PNEC = 100mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
Methyl alcohol	PNEC = 2.08mg/L	PNEC = 7.7mg/kg			

# SAFETY DATA SHEET

Ethanol, denat. with 5% wood spirit

Revision Date 29-Sep-2023

67-56-1 ( 5 )		sediment dw			
---------------	--	-------------	--	--	--

## 8.2. Exposure controls

### Engineering Measures

Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

### Personal protective equipment

**Eye Protection** Goggles (European standard - EN 166)

**Hand Protection** Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Viton (R)	See manufacturers recommendations	-	EN 374	(minimum requirement)

**Skin and body protection** Long sleeved clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

**Respiratory Protection** When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

**Large scale/emergency use** Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced  
**Recommended Filter type:** Organic gases and vapours filter Type A Brown conforming to EN14387

**Small scale/Laboratory use** Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.  
**Recommended half mask:-** Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141  
When RPE is used a face piece Fit Test should be conducted

**Environmental exposure controls** Prevent product from entering drains. Do not allow material to contaminate ground water system.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

<b>Physical State</b>	Liquid
<b>Appearance</b>	Colorless
<b>Odor</b>	No information available
<b>Odor Threshold</b>	No data available
<b>Melting Point/Range</b>	-117 °C / -178.6 °F
<b>Softening Point</b>	No data available
<b>Boiling Point/Range</b>	78 °C / 172.4 °F

# SAFETY DATA SHEET

Ethanol, denat. with 5% wood spirit

Revision Date 29-Sep-2023

<b>Flammability (liquid)</b>	Highly flammable	On basis of test data
<b>Flammability (solid,gas)</b>	Not applicable	Liquid
<b>Explosion Limits</b>	<b>Lower</b> 3.4 vol% <b>Upper</b> 19 vol%	
<b>Flash Point</b>	12 °C / 53.6 °F	<b>Method</b> - No information available
<b>Autoignition Temperature</b>	370 °C / 698 °F	
<b>Decomposition Temperature</b>	No data available	
<b>pH</b>	No information available	
<b>Viscosity</b>	No data available	
<b>Water Solubility</b>	Completely soluble	
<b>Solubility in other solvents</b>	No information available	
<b>Partition Coefficient (n-octanol/water)</b>		
<b>Component</b>	<b>log Pow</b>	
Ethyl alcohol	-0.32	
Methyl alcohol	-0.74	
<b>Vapor Pressure</b>	No data available	
<b>Density / Specific Gravity</b>	0.800	
<b>Bulk Density</b>	Not applicable	Liquid
<b>Vapor Density</b>	No data available	(Air = 1.0)
<b>Particle characteristics</b>	Not applicable (liquid)	

## 9.2. Other information

<b>Molecular Formula</b>	C2 H6 O
<b>Molecular Weight</b>	46.06
<b>Explosive Properties</b>	Vapors may form explosive mixtures with air

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

None known, based on information available

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

<b>Hazardous Polymerization</b>	Hazardous polymerization does not occur.
<b>Hazardous Reactions</b>	None under normal processing.

### 10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition. Incompatible products.

### 10.5. Incompatible materials

Acids. Strong oxidizing agents. Ammonia. Peroxides. Acid anhydrides. Acid chlorides.  
Metals.

### 10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Product Information

ACR36578

# SAFETY DATA SHEET

Ethanol, denat. with 5% wood spirit

Revision Date 29-Sep-2023

**(a) acute toxicity;**

<b>Oral</b>	Category 4
<b>Dermal</b>	Based on available data, the classification criteria are not met
<b>Inhalation</b>	Based on available data, the classification criteria are not met

**Toxicology data for the components**

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethyl alcohol	LD50 = 10470 mg/kg OECD 401 (Rat) 3450 mg/kg ( Mouse )	-	LC50 = 117-125 mg/l (4h) OECD 403 (rat) 20000 ppm/10H (rat)
Methyl alcohol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg ( Rabbit )	LC50 = 128.2 mg/L ( Rat ) 4 h

**(b) skin corrosion/irritation;** No data available

**(c) serious eye damage/irritation;** Category 2

**(d) respiratory or skin sensitization;**

<b>Respiratory</b>	No data available
<b>Skin</b>	No data available

Component	Test method	Test species	Study result
Ethyl alcohol 64-17-5 ( 95 )	Mouse Ear Swelling Test (MEST)	mouse	non-sensitising
	----- OECD Test Guideline 429 Local Lymph Node Assay	mouse	non-sensitising
Methyl alcohol 67-56-1 ( 5 )	OECD Test Guideline 406 Guinea Pig Maximisation Test (GPMT)	guinea pig	non-sensitising

**(e) germ cell mutagenicity;** No data available

Component	Test method	Test species	Study result
Ethyl alcohol 64-17-5 ( 95 )	AMES test OECD Test Guideline 471	in vitro Bacteria	negative
	----- Gene cell mutation OECD Test Guideline 476	in vitro Mammalian	negative

Not mutagenic in AMES Test

**(f) carcinogenicity;** No data available

The table below indicates whether each agency has listed any ingredient as a carcinogen

**(g) reproductive toxicity;** No data available

Component	Test method	Test species / Duration	Study result
Ethyl alcohol 64-17-5 ( 95 )	OECD Test Guideline 416 ----- OECD Test Guideline 414	Oral / mouse 2 Generation ----- Inhalation / Rat	NOAEL = 13.8 g/kg/day ----- NOAEC = 16000 ppm
Methyl alcohol 67-56-1 ( 5 )	OECD Test Guideline 416	Rat / Inhalation 2 Generation	NOAEC = 1.3 mg/l (air)

**(h) STOT-single exposure;** Category 2

**Results / Target organs** Optic nerve, Central nervous system (CNS).



# SAFETY DATA SHEET

Ethanol, denat. with 5% wood spirit

Revision Date 29-Sep-2023

(i) STOT-repeated exposure; No data available

Target Organs No information available.

(j) aspiration hazard; No data available

Other Adverse Effects The toxicological properties have not been fully investigated.

Symptoms / effects, both acute and delayed Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

## 11.2. Information on other hazards

**Endocrine Disrupting Properties** Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

#### Ecotoxicity effects

Contains a substance which is: Toxic to aquatic organisms. The product contains following substances which are hazardous for the environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Ethyl alcohol	Fathead minnow (Pimephales promelas) LC50 = 14200 mg/l/96h	EC50 = 9268 mg/L/48h EC50 = 10800 mg/L/24h	EC50 (72h) = 275 mg/l (Chlorella vulgaris)
Methyl alcohol	Pimephales promelas: LC50 > 10000 mg/L 96h	EC50 > 10000 mg/L 24h	

Component	Microtox	M-Factor
Ethyl alcohol	Photobacterium phosphoreum: EC50 = 34634 mg/L/30 min Photobacterium phosphoreum: EC50 = 35470 mg/L/5 min	
Methyl alcohol	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	

### 12.2. Persistence and degradability

Readily biodegradable

#### Persistence

Persistence is unlikely, based on information available.

Component	Degradability
Ethyl alcohol 64-17-5 (95)	OECD 301E = 94%
Methyl alcohol 67-56-1 (5)	DT50 ~ 17.2d >94% after 20d

#### Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

### 12.3. Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Ethyl alcohol	-0.32	No data available
Methyl alcohol	-0.74	<10 dimensionless

### 12.4. Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all

# SAFETY DATA SHEET

Ethanol, denat. with 5% wood spirit

Revision Date 29-Sep-2023

surfaces Will likely be mobile in the environment due to its volatility. Disperses rapidly in air

## 12.5. Results of PBT and vPvB assessment

No data available for assessment.

## 12.6. Endocrine disrupting properties

### **Endocrine Disruptor Information**

This product does not contain any known or suspected endocrine disruptors

## 12.7. Other adverse effects

### **Persistent Organic Pollutant**

This product does not contain any known or suspected substance

### **Ozone Depletion Potential**

This product does not contain any known or suspected substance

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

#### **Waste from Residues/Unused Products**

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

#### **Contaminated Packaging**

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

#### **European Waste Catalogue (EWC)**

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

#### **Other Information**

Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations.

## SECTION 14: TRANSPORT INFORMATION

### IMDG/IMO

<u>14.1. UN number</u>	UN1170
<u>14.2. UN proper shipping name</u>	ETHANOL
<u>14.3. Transport hazard class(es)</u>	3
<u>14.4. Packing group</u>	II

### ADR

<u>14.1. UN number</u>	UN1170
<u>14.2. UN proper shipping name</u>	ETHANOL
<u>14.3. Transport hazard class(es)</u>	3
<u>14.4. Packing group</u>	II

### IATA

<u>14.1. UN number</u>	UN1170
<u>14.2. UN proper shipping name</u>	ETHANOL
<u>14.3. Transport hazard class(es)</u>	3

# SAFETY DATA SHEET

Ethanol, denat. with 5% wood spirit

Revision Date 29-Sep-2023

- 14.4. Packing group** II
- 14.5. Environmental hazards** No hazards identified
- 14.6. Special precautions for user** No special precautions required.
- 14.7. Maritime transport in bulk according to IMO instruments** Not applicable, packaged goods

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Ethyl alcohol	64-17-5	200-578-6	-	-	X	X	KE-13217	X	X
Methyl alcohol	67-56-1	200-659-6	-	-	X	X	KE-23193	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Ethyl alcohol	64-17-5	X	ACTIVE	X	-	X	X	X
Methyl alcohol	67-56-1	X	ACTIVE	X	-	X	X	X

**Legend:** X - Listed '-' - Not Listed

**KECL** - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

#### Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Ethyl alcohol	64-17-5	-	-	-
Methyl alcohol	67-56-1	-	Use restricted. See item 69. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-

#### REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

#### Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Ethyl alcohol	64-17-5	Not applicable	Not applicable
Methyl alcohol	67-56-1	500 tonne	5000 tonne

#### Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

# SAFETY DATA SHEET

Ethanol, denat. with 5% wood spirit

Revision Date 29-Sep-2023

## Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

## National Regulations

**UK** - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

## WGK Classification

Water endangering class = 2 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Ethyl alcohol	WGK1	
Methyl alcohol	WGK 2	Class I : 20 mg/m <sup>3</sup> (Massenkonzentration)

Component	France - INRS (Tables of occupational diseases)
Ethyl alcohol	Tableaux des maladies professionnelles (TMP) - RG 84
Methyl alcohol	Tableaux des maladies professionnelles (TMP) - RG 84

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Ethyl alcohol 64-17-5 ( 95 )		Group I	
Methyl alcohol 67-56-1 ( 5 )	Prohibited and Restricted Substances	Group I	

## 15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

## SECTION 16: OTHER INFORMATION

### Full text of H-Statements referred to under sections 2 and 3

H302 - Harmful if swallowed  
H319 - Causes serious eye irritation  
H371 - May cause damage to organs  
H225 - Highly flammable liquid and vapor  
H301 - Toxic if swallowed  
H311 - Toxic in contact with skin  
H331 - Toxic if inhaled  
H370 - Causes damage to organs

### Legend

**CAS** - Chemical Abstracts Service

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical

# SAFETY DATA SHEET

Ethanol, denat. with 5% wood spirit

Revision Date 29-Sep-2023

Substances/EU List of Notified Chemical Substances

**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**ENCS** - Japanese Existing and New Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

**WEL** - Workplace Exposure Limit

**TWA** - Time Weighted Average

**ACGIH** - American Conference of Governmental Industrial Hygienists

**IARC** - International Agency for Research on Cancer

**DNEL** - Derived No Effect Level

Predicted No Effect Concentration (PNEC)

**RPE** - Respiratory Protective Equipment

**LD50** - Lethal Dose 50%

**LC50** - Lethal Concentration 50%

**EC50** - Effective Concentration 50%

**NOEC** - No Observed Effect Concentration

**POW** - Partition coefficient Octanol:Water

**PBT** - Persistent, Bioaccumulative, Toxic

**vPvB** - very Persistent, very Bioaccumulative

**ADR** - European Agreement Concerning the International Carriage of Dangerous Goods by Road

**ICAO/IATA** - International Civil Aviation Organization/International Air Transport Association

**IMO/IMDG** - International Maritime Organization/International Maritime Dangerous Goods Code

**MARPOL** - International Convention for the Prevention of Pollution from Ships

**OECD** - Organisation for Economic Co-operation and Development

**ATE** - Acute Toxicity Estimate

**BCF** - Bioconcentration factor

**VOC** - (Volatile Organic Compound)

## Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

## Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

**Physical hazards** On basis of test data

**Health Hazards** Calculation method

**Environmental hazards** Calculation method

## Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

**Creation Date** 25-Nov-2010

**Revision Date** 29-Sep-2023

**Revision Summary** Not applicable.

**This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.**

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**